

HAZARD STATEMENTS

PRECAUTIONARY STATEMENTS-PREVENTION

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required.

PRECAUTIONARY STATEMENTS-RESPONSE

If exposed or concerned, get medical advice or attention.

FIRST AID MEASURES

GENERAL ADVICE: If exposed or concerned, get medical advice or attention.

EYE CONTACT: Rinse thoroughly with plenty of water, also under the eyelids. If eye irritation persists, get medical advice or attention.

SKIN CONTACT: Wash off immediately with plenty of water. If skin irritation persists, call a physician.

INHALATION: Remove to fresh air.

INGESTION: Induce vomiting, but only if victim is fully conscious. Call a physician.

MOST IMPORTANT SYMPTOMS AND EFFECTS

SYMPTOMS: Direct contact with eyes may cause temporary irritation.

INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION

AND SPECIAL TREATMENT NEEDED

NOTES TO PHYSICIAN: Treat symptomatically.

PRECAUTIONARY STATEMENTS-DISPOSAL

Dispose of contents or container to an approved waste disposal plant.

CONDITIONS FOR SAFE STORAGE,

INCLUDING ANY INCOMPATIBILITIES

Storage Conditions: Keep containers tightly closed in a dry, cool and well-ventilated place. Store locked up. Protect from excessive heat. Protect from freezing.

Incompatible Materials: None known based on information supplied.

WASTE TREATMENT METHODS

Disposal of Waste or Contaminated Packaging: Disposal should be in accordance with applicable regional, national and local laws and regulations.

Nanco™

PREMIER KOTE SUPER GLOSS FLOOR FINISH

SUPER ACABADO BRILLANTE PARA PISO

- Labor Saving High Performance - Intermediate Maintenance
 - Flexible Polymer Formula
 - Moderate Wear for Medium to Heavy Traffic Areas
 - Metal Interlocked Acrylic Thermoplastic Chemistry
 - High Durability and Gloss
 - Multipurpose
 - Use on Most Resilient Flooring, Terrazzo and More
- Easy to Use-Self Leveling, Self Sealing Spray Buffable and Restorable
- Versatile-Responds to Low or High Speed Buffing and Burnishing
- Fortified with OPTIMAX-Optical Brightener Performance

KEEP OUT OF REACH OF CHILDREN

See additional precautionary statements on side panel.

NET CONTENTS: 128 Fl. Oz. (1 Gal.) 3.78 liters

BEAUTY KOTE is designed to provide a durable, high gloss floor with a minimum amount of costs.

This high solids formula saves labor by reducing the time needed to apply, reapply.

With only 3 or 4 coats, the acrylic thermoplastic polymers in the formula create a beautiful floor without fear of difficulties in application. This easy leveling finish is specially designed for medium to heavy traffic areas with intermediate maintenance schedules. The highly versatile product can be maintained by low or high speed spray buffing and/or burnishing with moderately aggressive pads. The metal interlocked chemistry provides an extremely durable finish resistant to wear, scuffing, abrasions and marks while still versatile enough to use on a variety of surfaces including resilient flooring and terrazzo.

BEAUTY KOTE needs no sealer and is easy to apply with most types of applicators.

BEAUTY KOTE is ideal for use in schools, office and commercial buildings, government and institutional facilities, hospitals and health care facilities and more.

DIRECTIONS

BASE APPLICATION: Strip floor per the instructions on the floor stripper label. Apply this product in thin, light coats until a base of approximately 3-4 coats has been achieved. Use a clean synthetic mop and allow each coat to dry 30 minutes between applications.

MAINTENANCE: Remove all loose debris by sweeping and then dust mopping. Use a neutral pH cleaner either by mopping or automatic scrubber to clean the surface. This product will respond well to most any routine. Use of low or high speed machinery to spray buff or burnish will work to bring out the best in this finish.

TOPSCRUB AND RECOAT: Remove all loose debris by sweeping and then dust mopping. Use a heavy duty or concentrated neutral pH cleaner in an automatic scrubber with abrasive pad to clean the surface. Rinse thoroughly with clean water and allow to dry. Rebuild base by applying 2-3 thin coats with a synthetic mop allowing 30 minutes to dry between applications.

Manufactured for

9034 LONG POINT ROAD, BLDG B,

HOUSTON, TEXAS 77055

(713) 932-8293 • (800) 634-5816